


## HR snap shackle - With thimble eye - Length: 110 mm

Part #2495




### Description

HR Forged snap shackle (Grade 17.4 PH stainless steel) with thimble eye  
Allows to splice the halyard directly onto the snap shackle (without using a thimble)  
Avoids the wear of the ropes  
Free rotation of the snap shackle thanks to the swivel eye  
The plunger pin is set captive into the hook and cannot become detached  
Excellent working and breaking loads > Easy to open by pulling the plunger pin (possibility to attach a lanyard)

### Applications

Snap shackle applications  
Allows to splice the halyard  
Applications requiring a free rotation of the snap shackle (for a better sail orientation)

## Technical information

|   |                                  |
|---|----------------------------------|
| Materials   | HR 17.4 PH stainless steel grade |
| Length (mm)   | 110                              |
|  Working load (kg) | 1280                             |
| Breaking load (kg)  | 2400                             |
| Weight (g)  | 150                              |
| A (mm)  | 21                               |
| B (mm)  | 14                               |

### Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.  
The safety factor is 5 times the breaking load.  
 $WLL = \text{Breaking load} / 5$

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.