



STRUCTURAL FURLERS

© ANWB Audio Visuele Dienst /Dragonfly

STB / STG / FLT

24 to 35 feet units

Top stainless steel toggle Fixes the top swivel on to the mast (included)

Head swivel allows the wire to turn

FX+ swivel

Halyard swivel

Thrust bearing with Torlon® ball bearings. Twin rim joints proofing

Stainless steel wire ø 5 to ø 7 mm (not included)

Link plates Allows adjusting the length of the forestay that is easily removed. Ideal for unstepping operations)

Continuous line drum

Flat drum + carbon housing

Drum

Stainless steel toggle

STG 4,5

STB 3 T

FLT 1.5 / 2.5 / 5 T

STOCKEURS STG & STB

STB / STG avantages

- The STG & STB are wire structural furlers, that are light and easy to install.
- Sails luff fitted with hanks or a zip.
- Each kit model includes :
 - 1 x halyard swivel with top stainless steel toggle (rotation of the wire)
 - 1 x drum with S/s toggle to fit on the foredeck chain plate.

Features

- The STG is equipped with an head swivel, a halyard swivel and a continuous line drum for maximum luff.
- The STB is a wire structural furler, cheaper version, with a discontinuous drum and a head swivel.

Model	Boat length	Forestay diameter*	Working load (Tons)	ø Drum (drum)
STB 3T	7,5 → 9,5 meters	ø 5 mm ou ø 6 mm according to the type of boat	3 T	119 mm*
STG 3T				
STG 4T5	8 → 10 meters	ø 7 mm	4,5 T	227 mm

*Wire non delivered

FLT FLAT DRUM STRUCTURAL FURLERS

Perfect for racing boats : The FLT drum structural furler is compact, the discontinuous line is of vectran (diam. 5mm). The low profile mechanism offers a longer luff and its large diameter a strong furling power. It is easy to operate with the partially reduced diameter line.



FLT Kit = flat drum + masthead swivel



Model	Reference	Boat length	ø bottom pin (mm)	forestay* ø (mm)	SWL (tons)	ø drum (mm)
FLT 1T5	43311001540	6,5 → 7,5	ø 8	ø 5	1,5T	109
FLT 2T5	43311002540	7,5 → 9,5	ø 10	ø 6	2,5T	149
FLT 5T	43311005050	9 → 10,5	ø 12,7	ø 7-8	5T	200
FLT 5T	43311005040	10,5 → 12,5	ø 16	ø 10	5T	200